

Heavy Load Water Resistant High Temperature Extreme Stability

ULTRA CS-5 GREASE NLGI NO.2

With Maximum Moly Protection



ULTRA CS-5 GREASE *SUMMER FORMULA!*

Characteristics*

Ambient Range	F -22° to +122°
Ambient Range	C-30° to +50°
Operating Range	F -25° to +300°
Operating Range	C-32° to +149°
Base Fluid Type	Petroleum/ Mix
Thickener Type	Calcium Sulfonate Complex
Color	Dark Gray
% Molybdenum disulfide	5
Worked Penetration (mm)	265-295
% Change/100,000 stroke	+/-5
Roll Stability w/H2O % Change	+/-5
Viscosity @ 100°C, cSt	+/- 11.5
Viscosity @ 40°C, cSt	+/- 150
4 Ball Wear (mm) Max, Typ.	0.5
4 Ball E.P. Weld Point (kg) Min.	620
Timken E.P. Test OK load (lb) Typ.	60
Oxidation-psi drop/500 hr Max	N/A
Rust Test	Pass
Salt Fog Test, hours	+1100
Copper Corrosion	1a
Dropping Point	+288°C (+550°F)

NLGI. 2 (Summer)

Construction and Mining Grease

Calcium Sulfonate Complex with 5% Molybdenum

Contains 5% moly to minimize wear on heavy duty construction equipment. Meets or exceeds the requirements for **Caterpillar MPMG**, John Deere , FMC, and Mack FG-C. Exceptional performance for ball joints and pin and bushing applications. Recommended where high temperature and water contamination may be a concern. Will not soften when introduced to water. Superior load carrying Capabilities. For use in heavy equipment, on and off road trucks, agriculture and mining equipment.

FOR INFORMATION:

BROWN'S OIL SERVICE

4800 Van Cleave St Indianapolis, IN 46226

Phone: 317-545-OILS

35lb PAIL 120lb KEG 400lb DRUM